IECEE OD-2020-F1:2017© IEC 2017 TRF Template



Test Report issued under the responsibility of:



TEST REPORT IEC 60598-2-3 Luminaires Part 2: Particular requirements Section 3: Luminaires for road and street lighting

Report Number	CN21NN6Y 002
Date of issue	2021.10.12
Total number of pages:	11 pages
Name of Testing Laboratory preparing the Report:	TÜV Rheinland (Shanghai) Co., Ltd. No. 177, 178, Lane 777 West Guangzhong Road Jing'an District Shanghai CHINA
Applicant's name:	Jiangsu Sokoyo Solar Lighting Co., Ltd.
Address:	West Guoji Industry Park, Northern Suburb of Yangzhou City, Jiangsu, P.R. China
Test specification:	
Standard:	IEC 60598-2-3:2002, AMD1:2011 used in conjunction with IEC 60598-1:2014, AMD1:2017
Test procedure	CB Scheme
Non-standard test method	N/A
Test Report Form No	IEC60598_2_3L
Test Report Form(s) Originator:	Intertek Semko AB
Master TRF	Dated 2018-03-09
Copyright © 2018 IEC System of Co Equipment and Components (IECE	nformity Assessment Schemes for Electrotechnical E System). All rights reserved.
	in part for non-commercial purposes as long as the IECEE is acknowledged as CEE takes no responsibility for and will not assume liability for damages resulting ad material due to its placement and context.
If this Test Report Form is used by no CB Scheme procedure shall be removed	n-IECEE members, the IECEE/IEC logo and the reference to the red.
	Report unless signed by an approved CB Testing Laboratory te issued by an NCB in accordance with IECEE 02.
General disclaimer:	
	t relate only to the object tested. cept in full, without the written approval of the Issuing CB Testing at Report and its contents can be verified by contacting the NCB,

Disclaimer: This document is controlled and has been released electronically. Only the version on the IECEE Website is the current document version

Test item description:	LED Street Light
Trade Mark:	SOKOYO°
Manufacturer:	Jiangsu Sokoyo Solar Lighting Co., Ltd.
Model/Type reference::	KY-F-XC-001,KY-F-XC-002,KY-F-HX-001,KY-F-HX-002 KY-F-HX-003,KY-F-HX-004 details see model list on page 7
Ratings:	Class III; IP65; ta=35°C details see 'General product information'

Responsible Testing Laboratory (as applicable), testing procedure and testing location(s):

\boxtimes	CB Testing Laboratory:	TÜV Rheinland (Shan	ghai) Co., Ltd.
Testing location/address:		No. 177, 178, Lane 777 West Guangzhong Road Jing'an District Shanghai CHINA	
Tes	ted by (name, function, signature):	Mark Geng/Trainee Fernando Dai / PE	Mark Geng Fernando Dei Mark for
Арр	roved by (name, function, signature):	Alex Yan / Reviewer	Mex for
			
	Testing procedure: CTF Stage 1:		
Tes	ting location/address:	N/A	
Tes	ted by (name, function, signature):	N/A	
Арр	roved by (name, function, signature) :	N/A	
	Testing procedure: CTF Stage 2:		
Tes	ting location/address:	N/A	
Tes	ted by (name + signature)	N/A	
Wit	nessed by (name, function, signature).:	N/A	
Арр	roved by (name, function, signature):	N/A	
	Testing procedure: CTF Stage 3:		
	Testing procedure: CTF Stage 4:		
Tes	ting location/address	N/A	
Tes	ted by (name, function, signature):	N/A	
Wit	nessed by (name, function, signature). :	N/A	
Арр	roved by (name, function, signature):	N/A	
Sup	ervised by (name, function, signature):	N/A	

List of Attachments (including a total number of pages in each attachment): N/A			
Summary of testing:			
Tests performed (name of test and test clause): Clause 3 according to IEC 60598-2-3:2002, AMD1:2011 used in conjunction with IEC 60598- 1:2014, AMD1:2017 were performed in TÜV Rheinland (Shanghai) Co., Ltd.	Testing location: TÜV Rheinland (Shanghai) Co., Ltd. No. 177, 178, Lane 777 West Guangzhong Road Jing'an District Shanghai CHINA		
Summary of compliance with National Differenc	es:		

Copy of marking plate:

The artwork below may be only a draft. The use of certification marks on a product must be authorized by the respective NCBs that own these marks.

Take model KY-Y-YJ-004 as example

LED Street Light Jiangsu Sokoyo Solar Lighting Co., Ltd. Model: KY-Y-YJ-004 Input: DC48V Current: 1.66A Power:80W Ta:35°C Class III

Model name	Input voltage (dc)	Rated current	Rating Wattage
KY-F-XC-001	36V	1,11A	40W
KY-F-XC-002	36V	1,67A	60W
KY-F-HX-001	42V	1,91A	80W
KY-F-HX-002	48V	2,08A	100W
KY-F-HX-003	48V	2,5A	120W
KY-F-HX-004	48V	3,13A	150W
KY-F-FY-001	30V	1,33A	40W
KY-F-FY-002	48V	1,25A	60W
KY-F-JX-001	48V	1,25A	60W
KY-F-HT-001	42V	1,91A	80W
KY-F-HT-002	48V	2,08A	100W
KY-F-HT-003	48V	2,5A	120W
KY-E-FY-001	30V	1,33A	40W
KY-E-JX-001	30V	1,33A	40W
KY-E-HT-001	42V	0,95A	40W
KY-E-HT-002	42V	1,19A	50W
KY-E-HT-003	42V	1,43A	60W
KY-E-HT-004	42V	1,67A	70W
KY-Y-YF-001	30V	1A	30W
KY-Y-YF-002	30V	1,33A	40W
KY-Y-YF-003	30V	1,67A	50W
KY-Y-YF-004	30V	2A	60W
KY-Y-YJ-001	48V	1,25A	60W
KY-Y-YJ-002	42V	1,91A	80W
KY-Y-YJ-003	48V	2,5A	120W
KY-Y-YJ-004	48V	1,66A	80W
KY-D-HY-001	30V	1,33A	40W
KY-D-XC-001	36V	1,67A	60W
KY-D-HX-001	42V	1,91A	80W
KY-D-HX-002	48V	2,08A	100W
KY-D-HX-003	48V	2,5A	120W
KY-D-HX-004	48V	3,13A	150W

TRF No. IEC60598_2_3L

		Page 5 of 11		Report No. CN21NN6Y 00
KY-D-I	-IX-005	48V	3,75A	180W
KY-D-I	-IX-006	48V	4,17A	200W
KY-D-I	-IX-007	48V	5A	240W

The height of letters and numerals shall not be less than 2mm.

The height of graphical symbols shall not be less than 5 mm.

The height of symbol of WEEE shall not be less than 7 mm.

Test item particulars:	LED Street Light		
Classification of installation and use:	Class III		
Supply Connection:	DC connector		
:			
Possible test case verdicts:			
- test case does not apply to the test object:	N/A		
- test object does meet the requirement:	P (Pass)		
- test object does not meet the requirement:	F (Fail)		
Testing:			
Date of receipt of test item:	2021.09.10		
Date (s) of performance of tests:	2021.10.10		
General remarks:			
"(See Enclosure #)" refers to additional information appended to the report. "(See appended table)" refers to a table appended to the report.			
Throughout this report a 🛛 comma / 🗌 point is u			
	sed as the decimal separator.		
Throughout this report a 🛛 comma / 🗌 point is u	sed as the decimal separator.		
Throughout this report a 🛛 comma / 🗌 point is u Clause numbers between brackets refer to clauses	sed as the decimal separator. in IEC 60598-1 IECEE 02: Yes Not applicable		
Throughout this report a ⊠ comma / □ point is u Clause numbers between brackets refer to clauses Manufacturer's Declaration per sub-clause 4.2.5 of The application for obtaining a CB Test Certificate includes more than one factory location and a declaration from the Manufacturer stating that the sample(s) submitted for evaluation is (are) representative of the products from each factory has	sed as the decimal separator. in IEC 60598-1 IECEE 02: Yes Not applicable		
Throughout this report a ⊠ comma / □ point is u Clause numbers between brackets refer to clauses Manufacturer's Declaration per sub-clause 4.2.5 of The application for obtaining a CB Test Certificate includes more than one factory location and a declaration from the Manufacturer stating that the sample(s) submitted for evaluation is (are) representative of the products from each factory has been provided	sed as the decimal separator. in IEC 60598-1 IECEE 02: Yes Not applicable the General product information section. Jiangsu Sokoyo Solar Lighting Co., Ltd.		
Throughout this report a ⊠ comma / □ point is u Clause numbers between brackets refer to clauses Manufacturer's Declaration per sub-clause 4.2.5 of The application for obtaining a CB Test Certificate includes more than one factory location and a declaration from the Manufacturer stating that the sample(s) submitted for evaluation is (are) representative of the products from each factory has been provided	sed as the decimal separator. in IEC 60598-1 IECEE 02: Yes Not applicable he General product information section.		
Throughout this report a ⊠ comma / □ point is u Clause numbers between brackets refer to clauses Manufacturer's Declaration per sub-clause 4.2.5 of The application for obtaining a CB Test Certificate includes more than one factory location and a declaration from the Manufacturer stating that the sample(s) submitted for evaluation is (are) representative of the products from each factory has been provided	sed as the decimal separator. in IEC 60598-1 IECEE 02: Yes Not applicable the General product information section. Jiangsu Sokoyo Solar Lighting Co., Ltd. West Guoji Industry Park, Northern Suburb of		

General product information:

This original test report CN21NN6Y 001 dated 2021.10.08 was modified on 2021.10.12 with the following changes:

Add new models KY-Y-YJ-004. It is same as previous certified model KY-Y-YJ-003 except lower rating. Model list:

Model name	Input voltage	Rating Wattage	Dimension (mm*mm*mm)	LED quantity	Pipe diameter (mm)
KY-Y-YJ-004	48Vdc	80W	680*1980*90	84	102

Clause 3 according to IEC 60598-2-3:2002, AMD1:2011 used in conjunction with IEC 60598-1:2014, AMD1:2017 were tested and passed

History:

Report No.: CN21NN6Y 001 date 2021.10.08, original report.

Report No.: CN21NN6Y 002 date 2021.10.12, technical modification.

IEC 60598-2-3			
Clause	Requirement + Test	Result - Remark	Verdict

3.2 (0)	GENERAL TEST REQUIREMENTS		Р
3.2 (0.3)	More sections applicable:	Yes □ No ⊠ Section/s:	_
3.2 (0.5)	Components	(see Annex 1)	
3.2 (0.7)	Information for luminaire design in light sources standards		
3.2 (0.7.2)	Light source safety standard:	IEC 62031, IEC TR 62778	
	Luminaire design in the light source safety standard		Р

3.4 (2)	CLASSIFICATION OF LUMINAIRES		Р
3.4 (2.2)	Type of protection:	Class III	Р
3.4 (2.3)	Degree of protection:	IP65	
3.4 (2.4)	Luminaire suitable for direct mounting on normally flammable surfaces	Yes 🛛 No 🗆	
3.4 (2.5)	Luminaire for normal use:	Yes 🛛 No 🗆	
	Luminaire for rough service:	Yes 🗌 No 🖾	
3.4 (-)	Modes of installation of road or street lighting		
	a) on a pipe	Yes 🛛 No 🗆	
	b) on a mast arm	Yes 🛛 No 🗆	
	c) on a post top	Yes 🛛 No 🗆	
	d) on span or suspension wires	Yes 🗌 No 🖾	
	e) on a wall	Yes 🗆 No 🛛	

3.5 (3)	MARKING		Р
3.5 (3.2)	Mandatory markings		Р
	Position of the marking	Attached on the external surface / supply cord	Р
	Format of symbols/text		Р
3.5 (3.3)	Additional information		Р
	Language of instructions		Р
3.5 (3.3.1)	Combination luminaires		N/A
3.5 (3.3.2)	Nominal frequency in Hz		N/A
3.5 (3.3.3)	Operating temperature		N/A
3.5 (3.3.5)	Wiring diagram		N/A
3.5 (3.3.6)	Special conditions		N/A

TRF No. IEC60598_2_3L

IEC 60598-2-3					
Clause	Requirement + Test	Result - Remark	Verdict		
3.5 (3.3.7)	Metal halide lamp luminaire – warning		N/A		
3.5 (3.3.8)	Limitation for semi-luminaires		N/A		
3.5 (3.3.9)	Power factor and supply current		Р		
3.5 (3.3.10)	Suitability for use indoors		N/A		
3.5 (3.3.11)	Luminaires with remote control		N/A		
3.5 (3.3.12)	Clip-mounted luminaire – warning		N/A		
3.5 (3.3.13)	Specifications of protective shields		N/A		
3.5 (3.3.14)	Symbol for nature of supply		N/A		
3.5 (3.3.15)	Rated current of socket outlet		N/A		
3.5 (3.3.16)	Rough service luminaire		N/A		
3.5 (3.3.17)	Mounting instruction for type Y, type Z and some type X attachments	Туре Ү	Р		
3.5 (3.3.18)	Non-ordinary luminaires with PVC cable		N/A		
3.5 (3.3.19)	Protective conductor current in instruction if applicable		N/A		
3.5 (3.3.20)	Provided with information if not intended to be mounted within arm's reach		N/A		
3.5 (3.3.21)	Non-replaceable and non-user replaceable light sources information provided	non-user replaceable	Р		
3.5 (3.3.22)	Controllable luminaires, classification of insulation provided		N/A		
3.5 (3.3.23)	Luminaire without controlgear provided with necessary information for selection of appropriate component		N/A		
3.5 (3.3.24)	If not supplied with terminal block, information on the packaging		N/A		
3.5 (3.4)	Test with water		Р		
	Test with hexane		Р		
	Legible after test		Р		
	Label attached		Р		
3.5 (-)	Additional information in instruction leaflet		Р		
	a) Design attitude		Р		
	b) Weight		Р		
	c) Overall dimensions		Р		
	d) Maximum projected area if applicable		Р		
	e) Cross-sectional area of wires if applicable		N/A		
	f) Suitability for indoors use		N/A		

TRF No. IEC60598_2_3L

	IEC 60598-2-3		
Clause	Requirement + Test	Result - Remark	Verdict
	g) Dimensions of the compartment		N/A
	h) Torque setting to be applied to bolts or screws		Р
	i) Maximum mounting height		Р
3.6 (4)	CONSTRUCTION		N/A
3.7 (11)	CREEPAGE DISTANCES AND CLEARANCES		N/A
3.8 (7)	PROVISION FOR EARTHING		N/A
3.9 (14)	SCREW TERMINALS		N/A
3.9 (15)	SCREWLESS TERMINALS AND ELECTRICAL CO	NNECTIONS	N/A
3.10 (5)	EXTERNAL AND INTERNAL WIRING		N/A
3.11 (8)	PROTECTION AGAINST ELECTRIC SHOCK		N/A
3.12 (12)	ENDURANCE TEST AND THERMAL TEST		N/A
3.13 (9)	RESISTANCE TO DUST AND MOISTURE		N/A
3.14 (10)	INSULATION RESISTANCE AND ELECTRIC STRE	ENGTH	N/A

IEC 60598-2-3					
Clause	Requirement + Test	Result - Remark	Verdic		
3.15 (13)	RESISTANCE TO HEAT, FIRE AND TRACKING		N/A		
3.7 (11.2)	TABLE I: Creepage distances and clearances		N/A		
3.7 (11.2)	TABLE II: Creepage distances and clearances		N/A		
3.15 (13.2.1)	TABLE: Ball Pressure Test of Thermoplastics		N/A		
3.15	TABLE: Needle-flame test (IEC 60695-11-5)		N/A		
(13.3.1)					
3.15 (13.3.2)	TABLE: Glow-wire test (IEC 60695-2-11)		N/A		
3.15 (13.4)	TABLE: Proof tracking test (IEC 60112)		N/A		
ANNEX 1	TABLE: Critical components information		N/A		
ANNEX 2	TABLE: Thermal tests of Section 12		N/A		
ANNEX 2	TABLE: Thermal tests of Section 12		N/A		

ANNEX 3 Screw terminals (part of the luminaire) N/A	
---	--

ANNEX 4	Screwless terminals (part of the luminaire)	N/A
(15.6.3.1) (15.6.3.2)	TABLE: Contact resistance test / Heating tests	N/A

- End of test report --